

Gromacs 2018.6 for LX (intel)

Webpage

<http://www.gromacs.org/>

Version

2018.6

Build Environment

- ▶ Intel Parallel Studio XE 2018 update 4
- ▶ cmake 3.8.2

Files Required

- ▶ gromacs-2018.6.tar.gz
- ▶ regressiontests-2018.6.tar.gz

Build Procedure

```
#!/bin/sh

VERSION=2018.6
INSTALL_PREFIX=/local/apl/lx/gromacs2018.6

BASEDIR=/home/users/${USER}/Software/Gromacs/${VERSION}/
GROMACS_TARBALL=${BASEDIR}/gromacs-${VERSION}.tar.gz
REGRESSION_TARBALL=${BASEDIR}/regressiontests-${VERSION}.tar.gz
WORKDIR=/work/users/${USER}
REGRESSION_PATH=${WORKDIR}/regressiontests-${VERSION}

PARALLEL=12

#-----
umask 0022

module purge
module load intel_parallelstudio/2018update4
module load cmake/3.8.2

cd ${WORKDIR}
if [ -d gromacs-${VERSION} ]; then
  mv gromacs-${VERSION} gromacs_erase
  rm -rf gromacs_erase &
fi

if [ -d regressiontests-${VERSION} ]; then
  mv regressiontests-${VERSION} regressiontests_erase
  rm -rf regressiontests_erase &
fi

tar xzf ${GROMACS_TARBALL}
tar xzf ${REGRESSION_TARBALL}
cd gromacs-${VERSION}

# compiler setting
export CC=icc
export CXX=icpc
export F77=ifort
export F90=ifort
export FC=ifort

# single precision, no MPI
mkdir rccs-s
cd rccs-s
cmake .. \
  -DCMAKE_INSTALL_PREFIX=${INSTALL_PREFIX} \
  -DCMAKE_VERBOSE_MAKEFILE=ON \
  -DGMX_MPI=OFF \
  -DGMX_GPU=OFF \
  -DGMX_DOUBLE=OFF \
  -DGMX_THREAD_MPI=ON \
  -DGMX_FFT_LIBRARY=mkl \
  -DREGRESSIONTEST_DOWNLOAD=OFF \
  -DREGRESSIONTEST_PATH=${REGRESSION_PATH}
make -j${PARALLEL} && make check && make install
cd ..

# double precision, no MPI
mkdir rccs-d
cd rccs-d
cmake .. \
```

```
-DCMAKE_INSTALL_PREFIX=${INSTALL_PREFIX} \  
-DCMAKE_VERBOSE_MAKEFILE=ON \  
-DGMX_MPI=OFF \  
-DGMX_GPU=OFF \  
-DGMX_DOUBLE=ON \  
-DGMX_THREAD_MPI=ON \  
-DGMX_FFT_LIBRARY=mkl \  
-DREGRESSIONTEST_DOWNLOAD=OFF \  
-DREGRESSIONTEST_PATH=${REGRESSION_PATH}  
make -j${PARALLEL} && make check && make install  
cd ..  
  
# compiler setting for MPI versions  
export CC=mpiicc  
export CXX=mpiicpc  
export F77=mpiifort  
export F90=mpiifort  
export FC=mpiifort  
  
# single precision, with MPI  
mkdir rccs-mpi-s  
cd rccs-mpi-s  
cmake .. \  
-DCMAKE_INSTALL_PREFIX=${INSTALL_PREFIX} \  
-DCMAKE_VERBOSE_MAKEFILE=ON \  
-DGMX_MPI=ON \  
-DGMX_GPU=OFF \  
-DGMX_DOUBLE=OFF \  
-DGMX_THREAD_MPI=OFF \  
-DGMX_FFT_LIBRARY=mkl \  
-DREGRESSIONTEST_DOWNLOAD=OFF \  
-DREGRESSIONTEST_PATH=${REGRESSION_PATH}  
make -j${PARALLEL} && make check && make install  
cd ..  
  
# double precision, with MPI  
mkdir rccs-mpi-d  
cd rccs-mpi-d  
cmake .. \  
-DCMAKE_INSTALL_PREFIX=${INSTALL_PREFIX} \  
-DCMAKE_VERBOSE_MAKEFILE=ON \  
-DGMX_MPI=ON \  
-DGMX_GPU=OFF \  
-DGMX_DOUBLE=ON \  
-DGMX_THREAD_MPI=OFF \  
-DGMX_FFT_LIBRARY=mkl \  
-DREGRESSIONTEST_DOWNLOAD=OFF \  
-DREGRESSIONTEST_PATH=${REGRESSION_PATH}  
make -j${PARALLEL} && make check && make install  
cd ..
```