

## Gromacs 2019.2 for LX (gcc)

### ウェブページ

<http://www.gromacs.org/>

### バージョン

2019.2

### ビルド環境

- Intel Parallel Studio XE 2018 update 4 (intel MPI & MKL)
- gcc 7.3.1 (devtoolset-7 Software Collections)
- cmake 3.8.2

### ビルドに必要なファイル

- gromacs-2019.2.tar.gz
- regressiontests-2019.2.tar.gz

### ビルド手順

```
#!/bin/sh

VERSION=2019.2
INSTALL_PREFIX=/local/apl/lx/gromacs2019.2-gnu

BASEDIR=/home/users/${USER}/Software/Gromacs/${VERSION}/
GROMACS_TARBALL=${BASEDIR}/gromacs-${VERSION}.tar.gz
REGRESSION_TARBALL=${BASEDIR}/regressiontests-${VERSION}.tar.gz
WORKDIR=/work/users/${USER}
REGRESSION_PATH=${WORKDIR}/regressiontests-${VERSION}

PARALLEL=12

#-----
umask 0022

module purge
module load scl/devtoolset-7
module load intel_parallelstudio/2018update4
module load cmake/3.8.2

cd ${WORKDIR}
if [ -d gromacs-${VERSION} ]; then
  mv gromacs-${VERSION} gromacs_erase
  rm -rf gromacs_erase &
fi

if [ -d regressiontests-${VERSION} ]; then
  mv regressiontests-${VERSION} regressiontests_erase
  rm -rf regressiontests_erase &
fi

tar xzf ${GROMACS_TARBALL}
tar xzf ${REGRESSION_TARBALL}
cd gromacs-${VERSION}

# single precision, no MPI
mkdir rccs-s
cd rccs-s
cmake .. \
  -DCMAKE_INSTALL_PREFIX=${INSTALL_PREFIX} \
```

```
-DCMAKE_VERBOSE_MAKEFILE=ON \  
-DGMX_MPI=OFF \  
-DGMX_GPU=OFF \  
-DGMX_DOUBLE=OFF \  
-DGMX_THREAD_MPI=ON \  
-DGMX_BUILD_OWN_FFTW=ON \  
-DREGRESSIONTEST_DOWNLOAD=OFF \  
-DREGRESSIONTEST_PATH=${REGRESSION_PATH}  
make -j${PARALLEL} && make check && make install  
cd ..
```

```
# double precision, no MPI  
mkdir rccs-d  
cd rccs-d  
cmake .. \  
-DCMAKE_INSTALL_PREFIX=${INSTALL_PREFIX} \  
-DCMAKE_VERBOSE_MAKEFILE=ON \  
-DGMX_MPI=OFF \  
-DGMX_GPU=OFF \  
-DGMX_DOUBLE=ON \  
-DGMX_THREAD_MPI=ON \  
-DGMX_BUILD_OWN_FFTW=ON \  
-DREGRESSIONTEST_DOWNLOAD=OFF \  
-DREGRESSIONTEST_PATH=${REGRESSION_PATH}  
make -j${PARALLEL} && make check && make install  
cd ..
```

```
# compiler setting for MPI versions  
export CC=mpicc  
export CXX=mpicxx  
export F77=mpif90  
export F90=mpif90  
export FC=mpif90
```

```
# single precision, with MPI  
mkdir rccs-mpi-s  
cd rccs-mpi-s  
cmake .. \  
-DCMAKE_INSTALL_PREFIX=${INSTALL_PREFIX} \  
-DCMAKE_VERBOSE_MAKEFILE=ON \  
-DGMX_MPI=ON \  
-DGMX_GPU=OFF \  
-DGMX_DOUBLE=OFF \  
-DGMX_THREAD_MPI=OFF \  
-DGMX_BUILD_OWN_FFTW=ON \  
-DREGRESSIONTEST_DOWNLOAD=OFF \  
-DREGRESSIONTEST_PATH=${REGRESSION_PATH}  
make -j${PARALLEL} && make check && make install  
cd ..
```

```
# double precision, with MPI  
mkdir rccs-mpi-d  
cd rccs-mpi-d  
cmake .. \  
-DCMAKE_INSTALL_PREFIX=${INSTALL_PREFIX} \  
-DCMAKE_VERBOSE_MAKEFILE=ON \  
-DGMX_MPI=ON \  
-DGMX_GPU=OFF \  
-DGMX_DOUBLE=ON \  
-DGMX_THREAD_MPI=OFF \  
-DGMX_BUILD_OWN_FFTW=ON \  
-DREGRESSIONTEST_DOWNLOAD=OFF \  
-DREGRESSIONTEST_PATH=${REGRESSION_PATH}  
make -j${PARALLEL} && make check && make install  
cd ..
```

