

Molpro 2021.3.1 (HPE)

ウェブページ

<https://www.molpro.net/>

バージョン

2021.3.1 (latest commit: Tue Nov 23 17:31:27 2021 +0100)

ビルド環境

- GCC 10.3.1 (gcc-toolset-10)
- GCC 11.2.1 (gcc-toolset-11)
- HPC-X 2.11
- openblas 0.3.15 (Rocky Linux 8 のもの)

ビルドに必要なファイル

- Molpro_release.tar.gz (ダウンロードした Molpro_release を tar.gz で固めたもの)
- ga-5.8.2.tar.gz
- work.patch
- patch-argos-binput.F
- patch-cic-ltfFortranInt.h
- patch-common_modules-common_cconf1
 - パッチファイルは /apl/molpro/2021.3.1/patches 以下にあります。内容はそちらでご確認ください。
- token

ビルド手順

```
#!/bin/sh

GA_VERSION=5.8.2
GA_ARCHIVE=/home/users/${USER}/Software/GlobalArrays/${GA_VERSION}/ga-${GA_VERSION}.tar.gz

MOLPRO_VERSION=2021.3.1
MOLPRO_DIRNAME=Molpro_release
PARALLEL=12
BASEDIR=/home/users/${USER}/Software/Molpro/${MOLPRO_VERSION}
MOLPRO_TARBALL=${BASEDIR}/${MOLPRO_DIRNAME}.tar.gz

PATCH_SNPRINTF=${BASEDIR}/secure_snprintf.patch
PATCH0=${BASEDIR}/work.patch
PATCH1=${BASEDIR}/patch-argos-binput.F
PATCH2=${BASEDIR}/patch-cic-ltfFortranInt.h
PATCH3=${BASEDIR}/patch-common_modules-common_cconf1

TOKEN=${BASEDIR}/token

WORKDIR=/gwork/users/${USER}
GA_INSTALLDIR=${WORKDIR}/ga-temporary
INSTALLDIR=/apl/molpro/${MOLPRO_VERSION}

#-----
umask 0022
ulimit -s unlimited

export LANG=
export LC_ALL=C
export OMP_NUM_THREADS=1

cd $WORKDIR
if [ -d ga-${GA_VERSION} ]; then
```

```

mv ga-${GA_VERSION} ga_tmp
rm -rf ga_tmp &
fi
if [ -d ga-temporary ]; then
  mv ga-temporary ga_tmp_tmp
  rm -rf ga_tmp_tmp &
fi
if [ -d ${MOLPRO_DIRNAME} ]; then
  mv ${MOLPRO_DIRNAME} molpro_tmp
  rm -rf molpro_tmp &
fi

module purge
module load gcc-toolset/10
module load openmpi/4.1.4-hpcx/gcc11

tar zxf ${GA_ARCHIVE}
cd ga-${GA_VERSION}

export CFLAGS="-mpc80"
export FFLAGS="-mpc80"
export FCFLAGS="-mpc80"
export CXXFLAGS="-mpc80"

export F77=mpif90
export F90=mpif90
export FC=mpif90
export CC=mpicc
export CXX=mpicxx
export MPIF77=mpif90
export MPICC=mpicc
export MPICXX=mpicxx
export GA_FOPT="-O3"
export GA_COPT="-O3"
export GA_CXXOPT="-O3"

./autogen.sh
./configure --enable-i8 \
  --with-mpi-pr \
  --prefix=${GA_INSTALLDIR}

make -j ${PARALLEL}
make check
make install
cp config.log ${GA_INSTALLDIR}

module switch gcc-toolset/11

cd ../
tar zxf ${MOLPRO_TARBALL}
cd ${MOLPRO_DIRNAME}

patch -p0 < ${PATCH0}
patch -p0 < ${PATCH1}
patch -p0 < ${PATCH2}
patch -p0 < ${PATCH3}

export PATH="${GA_INSTALLDIR}/bin:$PATH" # where ga-config exists

CPPFLAGS="-I${GA_INSTALLDIR}/include -l/usr/include/openblas" \
LDFLAGS="-L${GA_INSTALLDIR}/lib" \
./configure --prefix=${INSTALLDIR} \
  --with-lapack="-L/usr/lib64 -lopenblas" \
  --enable-slater

```

```
sed -i -e "s/-J\\.//\" CONFIG # ?  
  
make -j ${PARALLEL}  
cp $TOKEN lib/.token  
  
make tuning  
  
MOLPRO_OPTIONS="" make quicktest  
MOLPRO_OPTIONS="-n2" make test  
  
make install
```

メモ

- --enable-slater は有効にしたもの、やはり正常に動作していないように見える(NECシステム時と同様)
 - テストも失敗。(他のテストについては全て通過)