

Gromacs 2019.4 for LX (intel)

ウェブページ

<http://www.gromacs.org/>

バージョン

2019.4

ビルド環境

- ▶ Intel Parallel Studio XE 2018 update 4
- ▶ GCC 7.3.1 (Software Collections devtoolset-7)
- ▶ cmake 3.8.2

ビルドに必要なファイル

- ▶ gromacs-2019.4.tar.gz
- ▶ regressiontests-2019.4.tar.gz

ビルド手順

```
#!/bin/sh
VERSION=2019.4
INSTALL_PREFIX=/local/apl/lx/gromacs${VERSION}
BASEDIR=/home/users/${USER}/Software/Gromacs/${VERSION}/
GROMACS_TARBALL=${BASEDIR}/gromacs-${VERSION}.tar.gz
REGRESSION_TARBALL=${BASEDIR}/regressiontests-${VERSION}.tar.gz
WORKDIR=/work/users/${USER}
REGRESSION_PATH=${WORKDIR}/regressiontests-${VERSION}
PARALLEL=12
#-----
umask 0022
module purge
module load scl/devtoolset-7
module load intel_parallelstudio/2018update4
module load cmake/3.8.2
cd ${WORKDIR}
if [ -d gromacs-${VERSION} ]; then
  mv gromacs-${VERSION} gromacs_erase
  rm -rf gromacs_erase &
fi
if [ -d regressiontests-${VERSION} ]; then
  mv regressiontests-${VERSION} regressiontests_erase
  rm -rf regressiontests_erase &
fi
tar xzf ${GROMACS_TARBALL}
tar xzf ${REGRESSION_TARBALL}
cd gromacs-${VERSION}
# compiler setting
export CC=icc
export CXX=icpc
export F77=ifort
export F90=ifort
export FC=ifort
# single precision, no MPI
mkdir rccs-s
cd rccs-s
cmake .. \
  -DCMAKE_INSTALL_PREFIX=${INSTALL_PREFIX} \
  -DCMAKE_VERBOSE_MAKEFILE=ON \
  -DGMX_MPI=OFF \
  -DGMX_GPU=OFF \
  -DGMX_DOUBLE=OFF \
  -DGMX_THREAD_MPI=ON \
  -DGMX_BUILD_OWN_FFTW=ON \
  -DREGRESSIONTEST_DOWNLOAD=OFF \
  -DREGRESSIONTEST_PATH=${REGRESSION_PATH}
make -j${PARALLEL} && make check && make install
cd ..
# double precision, no MPI
mkdir rccs-d
```

```
cd rccs-d
cmake .. \
  -DCMAKE_INSTALL_PREFIX=${INSTALL_PREFIX} \
  -DCMAKE_VERBOSE_MAKEFILE=ON \
  -DGMX_MPI=OFF \
  -DGMX_GPU=OFF \
  -DGMX_DOUBLE=ON \
  -DGMX_THREAD_MPI=ON \
  -DGMX_BUILD_OWN_FFTW=ON \
  -DREGRESSIONTEST_DOWNLOAD=OFF \
  -DREGRESSIONTEST_PATH=${REGRESSION_PATH}
make -j${PARALLEL} && make check && make install
cd ..

# compiler setting for MPI versions
export CC=mpiicc
export CXX=mpiicpc
export F77=mpiifort
export F90=mpiifort
export FC=mpiifort

# single precision, with MPI
mkdir rccs-mpi-s
cd rccs-mpi-s
cmake .. \
  -DCMAKE_INSTALL_PREFIX=${INSTALL_PREFIX} \
  -DCMAKE_VERBOSE_MAKEFILE=ON \
  -DGMX_MPI=ON \
  -DGMX_GPU=OFF \
  -DGMX_DOUBLE=OFF \
  -DGMX_THREAD_MPI=OFF \
  -DGMX_BUILD_OWN_FFTW=ON \
  -DREGRESSIONTEST_DOWNLOAD=OFF \
  -DREGRESSIONTEST_PATH=${REGRESSION_PATH}
make -j${PARALLEL} && make check && make install
cd ..

# double precision, with MPI
mkdir rccs-mpi-d
cd rccs-mpi-d
cmake .. \
  -DCMAKE_INSTALL_PREFIX=${INSTALL_PREFIX} \
  -DCMAKE_VERBOSE_MAKEFILE=ON \
  -DGMX_MPI=ON \
  -DGMX_GPU=OFF \
  -DGMX_DOUBLE=ON \
  -DGMX_THREAD_MPI=OFF \
  -DGMX_BUILD_OWN_FFTW=ON \
  -DREGRESSIONTEST_DOWNLOAD=OFF \
  -DREGRESSIONTEST_PATH=${REGRESSION_PATH}
make -j${PARALLEL} && make check && make install
cd ..
```